



SAFETY DATA SHEET

ADAWALL LIQUID WATERPROOFER

1.0 IDENTIFICATION OF COMPOUND

ADAWALL LIQUID WATERPROOFER: Black bitumen paint for waterproofing and weather protection

Short Term Exposure Limit (STEL): 720mg/m³ 10 min STEL
Good working practice suggests that impervious gloves and goggles should be worn when handling this product. Wear suitable breathing apparatus in confined or poorly ventilated spaces.

1.10 IDENTIFICATION OF SUPPLIER

Adawall Construction Chemicals

Earl Russell Way

Lawrence Hill

Bristol

Telephone: 0117 9415495 Fax: 0117 9554807

2.00 COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No	Concentration (%w/w)
White Spirit	64742-82-1	< 50%

Hazard Symbol Xn

Risk Phrases

R10: Flammable

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R65: Harmful: may cause lung damage if swallowed

3.00 HAZARDS IDENTIFICATION

Flammable liquid and vapour. If swallowed will cause vomiting and diarrhoea. Minute amounts aspirated into the lungs during ingestion may cause severe pulmonary injury. Will remove the natural greases from the skin, which may result in dryness, cracking and dermatitis. May cause long term damage to the aquatic environment.

4.00 FIRST AID MEASURES

Eyes: Flush eyes with copious amounts of water. Seek medical advice if any irritation persists.

Skin: Remove contaminated clothing. Wash skin with soap and water. Seek medical advice if any irritation persists.

Inhalation: If inhalation of high concentrations of vapour should occur, remove victim from exposure. Obtain medical attention.

Ingestion: Do not induce vomiting. Wash out mouth with water, give 200-300 ml of water to drink and seek medical attention.

5.00 FIRE FIGHTING MEASURES

This product is combustible.

Extinguishing Media: Dry powder, foam, water fog or (for small fires) carbon dioxide.

Unsuitable Extinguishing Media: Water jets.

Special Hazards: Drums and other containers of product exposed to fire may explode. These may be cooled with water spray/fog equipment.

Special protective equipment: Wear suitable clothing to prevent eye/skin contact occurring.

6.00 ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear full protective clothing and goggles. The use of breathing apparatus in confined spaces is recommended. Remove sources of ignition.

Environmental Precautions: Do not allow product to enter drains or water courses. Advise local authorities if this is not possible.

Clean Up Methods: Recover all spillages using absorbent materials.

7.00 HANDLING AND STORAGE

Handling: Avoid contact with eyes/skin. Do not breathe vapour. Provide adequate ventilation, including local extraction if necessary. Use appropriate breathing apparatus if this is not possible.

Storage: Protect containers from heat and sources of ignition. Keep containers away from strong oxidising agents. Take precautionary measures against static discharges.

8.00 EXPOSURE CONTROLS / PERSONAL PROTECTION

White Spirit

Long term exposure limit (LTEL): 575mg/m³ 8hr TWA

